

View Online at <https://aerobasegroup.com/nsn/5970-01-333-6611>

Dielectric Withstanding Voltage In Volts:

200.0

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Main Body Inside Diameter:

1.120 inches as supplied

First Branch Inside Diameter:

1.060 inches as supplied

Second Branch Inside Diameter:

1.060 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

3.320 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.100 inches after unrestricted recovery

Second Branch Wall Thickness:

0.100 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

3.420 inches after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

22.5 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Internal adhesive coating

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corp

Material:

Plastic, polyolefin, rt-301, raychem corp

Style Designator:

Transition-y

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500