Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-335-4712

| Delickility Indicatory |
|--|
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 4.000 feet |
| Tempurature Rating: |
| -55.0 degrees celsius and 135.0 degrees celsius |
| Environmental Protection: |
| Flame resistant and corrosion resistant and mildew resistant and water resistant |
| Expanded Inside Diameter: |
| 0.500 inches |
| Recovered Inside Diameter: |
| 0.250 inches |
| Recovered Wall Thickness: |
| 0.025 inches |
| Heat Shrinkage Rating In Percent: |
| 50.0 |
| Min. Tensile Strength (psi): |
| 1500 pounds per square inch |
| Flexibility: |
| Flexible |
| Color: |
| White |
| Material: |
| Plastic, polyolefin, mil-i-23053/5, class 1 |
| Material: |
| Plastic cross-linked polyolefin |
| Style Designator: |
| Shrinkable |
| Dielectric Material Voltage Rating Per Unit Thickness: |
| 500.0 volts per military /0.001 inch/ |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Νο |
| Fiig: |
| A22500 |
| |
| |