

View Online at <https://aerobasegroup.com/nsn/5970-01-339-8238>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Inside Diameter:

2.130 inches as supplied 1.060 inches after unrestricted recovery

First Branch Inside Diameter:

1.000 inches as supplied 0.540 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

3.660 inches after unrestricted recovery

Main Body Wall Thickness:

0.180 inches after unrestricted recovery

First Branch Wall Thickness:

0.100 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.670 inches after unrestricted recovery

Main Bodylength:

5.830 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Special Features:

Inside adhesive coated

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin, rt-1304, raychem corp

Material:

Plastic, polyolefin, rt-1304, raychem corp

Style Designator:

Transition-45 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

225.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500