

View Online at <https://aerobasegroup.com/nsn/5970-01-340-7706>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 90.0 degrees celsius

Environmental Protection:

Mildew resistant

Main Body Inside Diameter:

1.000 inches as supplied

First Branch Inside Diameter:

0.460 inches as supplied

Second Branch Inside Diameter:

0.460 inches as supplied

Third Branch Inside Diameter:

0.460 inches as supplied

Fourth Branch Inside Diameter:

0.270 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of Second Branch:

2.830 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.770 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

Second Branch Wall Thickness:

0.060 inches after unrestricted recovery

Third Branch Wall Thickness:

0.060 inches after unrestricted recovery

Fourth Branch Wall Thickness:

0.060 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.040 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

45.0 after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

10.0 as supplied

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Inside adhesive coated

Flexibility:

Flexible

Color:

Black

Material:

Rubber, polychloroprene, mil-i-81765/2

Material:

Rubber, polychloroprene, mil-i-81765/2

Style Designator:

Transition-1 to 4 cables

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500