

View Online at <https://aerobasegroup.com/nsn/5970-01-341-4981>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant

Main Body Wall Thickness:

0.070 inches after unrestricted recovery

Main Bodylength:

1.850 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.160 inches as supplied 0.280 inches after unrestricted recovery

Main Body Large End Inside Diameter:

1.160 inches as supplied 0.710 inches after unrestricted recovery

Distance From Bottom Of Shoulder To Large End Of Main Body:

1.380 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

0.710 inches after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Tab located between exterior small diameter and large diameter with hole 0.080 in. Dia; inside diameter has lips; wall thickness on small end tapers to 0.040 in.; inside adhesive coated

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, elastomer, rt-1325, raychem corp

Material:

Plastic, elastomer, rt-1325, raychem corp

Style Designator:

Boot-straight

Dielectric Material Voltage Rating Per Unit Thickness:

300.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500