

View Online at <https://aerobasegroup.com/nsn/5970-01-341-4981>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-55.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant

**Main Body Wall Thickness:**

0.070 inches after unrestricted recovery

**Main Bodylength:**

1.850 inches after unrestricted recovery

**Main Body Small End Inside Diameter:**

1.160 inches as supplied 0.280 inches after unrestricted recovery

**Main Body Large End Inside Diameter:**

1.160 inches as supplied 0.710 inches after unrestricted recovery

**Distance From Bottom Of Shoulder To Large End Of Main Body:**

1.380 inches after unrestricted recovery

**Distance From Top Of Shoulder To Small End Of Main Body:**

0.710 inches after unrestricted recovery

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Special Features:**

Tab located between exterior small diameter and large diameter with hole 0.080 in. Dia; inside diameter has lips; wall thickness on small end tapers to 0.040 in.; inside adhesive coated

**Flexibility:**

Semirigid

**Color:**

Black

**Material:**

Plastic, elastomer, rt-1325, raychem corp

**Material:**

Plastic, elastomer, rt-1325, raychem corp

**Style Designator:**

Boot-straight

**Dielectric Material Voltage Rating Per Unit Thickness:**

300.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500