NSN 5970-01-341-4982

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-341-4982

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant

Large End Wall Thickness Of Main Body:

0.140 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.050 inches after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

1.890 inches after unrestricted recovery

Distance From Centerline Of Small End To Edge Of Large End:

0.970 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.580 inches as supplied0.280 inches after unrestricted recovery

Main Body Large End Inside Diameter:

1.180 inches as supplied0.880 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

0.490 inches after unrestricted recovery

Angle Between Large End And Small End Centerlines In Deg:

45.0 as supplied90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Semirigid

Height:

1.520 inches after unrestricted recovery

Color:

Black

Material:

Plastic, elastomer, rt-1325, raychem corp

Material:

Plastic, elastomer, rt-1325, raychem corp

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

300.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5970-01-341-4982

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500