

View Online at <https://aerobasegroup.com/nsn/5970-01-341-7804>

Reliability Indicator:

Not established

Tempurature Rating:

-75.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant and solvent resistant and water resistant

Large End Wall Thickness Of Main Body:

0.040 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.040 inches after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

0.680 inches after unrestricted recovery

Distance From Centerline Of Small End To Edge Of Large End:

0.610 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.700 inches as supplied 0.150 inches after unrestricted recovery

Main Body Large End Inside Diameter:

0.700 inches as supplied 0.310 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

0.170 inches after unrestricted recovery

Angle Between Large End And Small End Centerlines In Deg:

180.0 as supplied 90.0 after unrestricted recovery

Min. Tensile Strength (psi):

600 pounds per square inch

Flexibility:

Flexible

Height:

0.790 inches after unrestricted recovery

Color:

Black

Material:

Rubber, silicone, rt-602, raychem corp

Material:

Rubber, silicone, rt-602, raychem corp

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500