

View Online at <https://aerobasegroup.com/nsn/5970-01-341-7805>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-75.0 degrees celsius

**Environmental Protection:**

Flame resistant and mildew resistant and solvent resistant and water resistant

**Large End Wall Thickness Of Main Body:**

0.060 inches after unrestricted recovery

**Small End Wall Thickness Of Main Body:**

0.060 inches after unrestricted recovery

**Distance From Intersecting Centerlines To Edge Of Small End:**

1.060 inches after unrestricted recovery

**Distance From Centerline Of Small End To Edge Of Large End:**

0.730 inches after unrestricted recovery

**Main Body Small End Inside Diameter:**

1.180 inches as supplied 0.250 inches after unrestricted recovery

**Main Body Large End Inside Diameter:**

1.180 inches as supplied 0.560 inches after unrestricted recovery

**Distance From Top Of Shoulder To Small End Of Main Body:**

0.280 inches after unrestricted recovery

**Angle Between Large End And Small End Centerlines In Deg:**

180.0 as supplied 90.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

600 pounds per square inch

**Flexibility:**

Flexible

**Height:**

1.050 inches after unrestricted recovery

**Color:**

Black

**Material:**

Rubber, silicone, rt-602, raychem corp

**Material:**

Rubber, silicone, rt-602, raychem corp

**Style Designator:**

Boot-90 degrees

**Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500