

View Online at <https://aerobasegroup.com/nsn/5970-01-342-3893>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant and solvent resistant and water resistant

Distance From Centerline Of Main Body To End Of First Branch:

1.500 inches after unrestricted recovery

Main Body Inside Diameter:

1.200 inches as supplied 0.600 inches after unrestricted recovery

First Branch Inside Diameter:

0.700 inches as supplied 0.350 inches after unrestricted recovery

Main Body Wall Thickness:

0.090 inches as supplied 0.090 inches after unrestricted recovery

First Branch Wall Thickness:

0.050 inches as supplied 0.050 inches after unrestricted recovery

Main Bodylength:

3.170 inches as supplied 3.200 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

15.0 as supplied 90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Special Features:

Adhesive coated inside

Flexibility:

Flexible

Color:

Any acceptable

Material:

Plastic, polyolefin

Material:

Plastic polyolefin

Style Designator:

Transition-t

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500