NSN 5970-01-342-3893

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-342-3893

Reliability Indicator: Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Flame resistant and mildew resistant and solvent resistant and water resistant Distance From Centerline Of Main Body To End Of First Branch: 1.500 inches after unrestricted recovery Main Body Inside Diameter: 1.200 inches as supplied0.600 inches after unrestricted recovery **First Branch Inside Diameter:** 0.700 inches as supplied0.350 inches after unrestricted recovery Main Body Wall Thickness: 0.090 inches as supplied0.090 inches after unrestricted recovery **First Branch Wall Thickness:** 0.050 inches as supplied0.050 inches after unrestricted recovery Main Bodylength: 3.170 inches as supplied3.200 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 15.0 as supplied90.0 after unrestricted recovery Min. Tensile Strength (psi): 1200 pounds per square inch **Special Features:** Adhesive coated inside Flexibility: Flexible Color: Any acceptable Material: Plastic, polyolefin Material: Plastic polyolefin **Style Designator:** Transition-t **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5970-01-342-3893

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500