NSN 5970-01-343-1454

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-343-1454

Reliability Indicator: Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and water resistant Distance From Centerline Of Main Body To End Of First Branch: 1.960 inches after unrestricted recovery Main Body Inside Diameter: 2.310 inches as supplied0.790 inches after unrestricted recovery **First Branch Inside Diameter:** 1.520 inches as supplied0.790 inches after unrestricted recovery Main Body Wall Thickness: 0.060 inches after unrestricted recovery **First Branch Wall Thickness:** 0.060 inches after unrestricted recovery Main Bodylength: 3.920 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Inside adhesive coating Flexibility: Flexible Color: Black Material: Plastic, polyolefin, rt-1361, raychem corp Material: Plastic, polyolefin, rt-1361, raychem corp **Style Designator:** Transition-t **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5970-01-343-1454

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500