

View Online at <https://aerobasegroup.com/nsn/5970-01-343-1455>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Solvent resistant and mildew resistant and flame resistant and water resistant and petroleum resistant

Main Body Inside Diameter:

1.460 inches as supplied 0.740 inches after unrestricted recovery

First Branch Inside Diameter:

0.700 inches as supplied 0.380 inches after unrestricted recovery

Second Branch Inside Diameter:

0.700 inches as supplied 0.380 inches after unrestricted recovery

Third Branch Inside Diameter:

0.700 inches as supplied 0.380 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

2.900 inches after unrestricted recovery

Main Body Wall Thickness:

0.120 inches after unrestricted recovery

First Branch Wall Thickness:

0.070 inches after unrestricted recovery

Second Branch Wall Thickness:

0.070 inches after unrestricted recovery

Third Branch Wall Thickness:

0.070 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.420 inches after unrestricted recovery

Main Bodylength:

5.320 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

10.0 as supplied 30.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Inside adhesive coating

Flexibility:

Flexible

Color:

Black

Material:

Rubber, neoprene, rt-501, rayclad tubes inc

Material:

Rubber, neoprene, rt-501, rayclad tubes inc

Style Designator:

Transition-1 to 3 cables

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500