

View Online at <https://aerobasegroup.com/nsn/5970-01-343-1455>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-55.0 degrees celsius

**Environmental Protection:**

Solvent resistant and mildew resistant and flame resistant and water resistant and petroleum resistant

**Main Body Inside Diameter:**

1.460 inches as supplied 0.740 inches after unrestricted recovery

**First Branch Inside Diameter:**

0.700 inches as supplied 0.380 inches after unrestricted recovery

**Second Branch Inside Diameter:**

0.700 inches as supplied 0.380 inches after unrestricted recovery

**Third Branch Inside Diameter:**

0.700 inches as supplied 0.380 inches after unrestricted recovery

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

2.900 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.120 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.070 inches after unrestricted recovery

**Second Branch Wall Thickness:**

0.070 inches after unrestricted recovery

**Third Branch Wall Thickness:**

0.070 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:**

2.420 inches after unrestricted recovery

**Main Bodylength:**

5.320 inches after unrestricted recovery

**Angle Between Main Body And First Branch Centerlines In Deg:**

10.0 as supplied 30.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Special Features:**

Inside adhesive coating

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Rubber, neoprene, rt-501, rayclad tubes inc

**Material:**

Rubber, neoprene, rt-501, rayclad tubes inc

**Style Designator:**

Transition-1 to 3 cables

**Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500