NSN 5970-01-343-3506

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-343-3506

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 90.0 degrees celsius

Main Body Inside Diameter:

2.190 inches as supplied1.000 inches after unrestricted recovery

First Branch Inside Diameter:

1.060 inches as supplied0.490 inches after unrestricted recovery

Second Branch Inside Diameter:

1.060 inches as supplied0.490 inches after unrestricted recovery

Third Branch Inside Diameter:

1.060 inches as supplied0.490 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

4.060 inches after unrestricted recovery

First Branch Wall Thickness:

0.120 inches after unrestricted recovery

Second Branch Wall Thickness:

0.120 inches after unrestricted recovery

Third Branch Wall Thickness:

0.120 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

3.500 inches after unrestricted recovery

Main Bodylength:

7.560 inches after unrestricted recovery

Special Features:

Material polychloroprene

Flexibility:

Flexible

Material:

Plastic

Material:

Plastic

Style Designator:

Transition-1 to 3 cables

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500