Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-343-3506

R	eliability Indicator:
	lot established
т	empurature Rating:
	55.0 degrees celsius and 90.0 degrees celsius
	lain Body Inside Diameter:
	.190 inches as supplied1.000 inches after unrestricted recovery
	irst Branch Inside Diameter:
1	.060 inches as supplied0.490 inches after unrestricted recovery
	econd Branch Inside Diameter:
1	.060 inches as supplied0.490 inches after unrestricted recovery
	hird Branch Inside Diameter:
1	.060 inches as supplied0.490 inches after unrestricted recovery
D	istance From Intersecting Centerline Of Main Body To End Of First Branch:
4	.060 inches after unrestricted recovery
	irst Branch Wall Thickness:
0	.120 inches after unrestricted recovery
s	econd Branch Wall Thickness:
0	.120 inches after unrestricted recovery
т	hird Branch Wall Thickness:
0	.120 inches after unrestricted recovery
D	istance From Edge Of Main Body To Intersecting Centerlines:
3	.500 inches after unrestricted recovery
M	lain Bodylength:
7	.560 inches after unrestricted recovery
S	pecial Features:
N	laterial polychloroprene
F	lexibility:
F	lexible
Ν	laterial:
Ρ	lastic
Μ	laterial:
Ρ	lastic
S	tyle Designator:
Т	ransition-1 to 3 cables
S	helf Life:
N	l/a
U	nit Of Measure:
_	Demilitarization:
	0
	iig:
A	22500