

View Online at <https://aerobasegroup.com/nsn/5970-01-343-8486>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Inside Diameter:

1.460 inches as supplied 0.710 inches after unrestricted recovery

First Branch Inside Diameter:

1.000 inches as supplied 0.490 inches after unrestricted recovery

Second Branch Inside Diameter:

1.000 inches as supplied 0.490 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

3.220 inches after unrestricted recovery

Main Body Wall Thickness:

0.120 inches after unrestricted recovery

First Branch Wall Thickness:

0.100 inches after unrestricted recovery

Second Branch Wall Thickness:

0.100 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.580 inches after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

10.0 after unrestricted recovery and 22.5 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Inside adhesive coated

Flexibility:

Flexible

Color:

Black

Material:

Rubber, neoprene, rt-501, rayclad tubes inc

Material:

Rubber, neoprene, rt-501, rayclad tubes inc

Style Designator:

Transition-y

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500