

View Online at <https://aerobasegroup.com/nsn/5970-01-345-4244>

Reliability Indicator:

Not established

Temperature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Distance From Centerline Of Main Body To End Of First Branch:

1.000 inches after unrestricted recovery

Main Body Inside Diameter:

1.400 inches as supplied 0.700 inches after unrestricted recovery

First Branch Inside Diameter:

0.600 inches as supplied 0.300 inches after unrestricted recovery

Main Body Wall Thickness:

0.091 inches after unrestricted recovery

First Branch Wall Thickness:

0.058 inches after unrestricted recovery

Main Bodylength:

2.000 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

165.0 as supplied 90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Special Features:

Inside adhesive coated

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin, rt-1304, raychem corp

Material:

Plastic, polyolefin, rt-1304, raychem corp

Style Designator:

Transition-t

Dielectric Material Voltage Rating Per Unit Thickness:

225.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500