

View Online at <https://aerobasegroup.com/nsn/5970-01-346-2148>

**Reliability Indicator:**

Not established

**Temperature Rating:**

-55.0 degrees celsius and 90.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and mildew resistant

**Main Body Inside Diameter:**

0.700 inches as supplied 0.380 inches after unrestricted recovery

**First Branch Inside Diameter:**

0.460 inches as supplied 0.270 inches after unrestricted recovery

**Second Branch Inside Diameter:**

0.460 inches as supplied 0.270 inches after unrestricted recovery

**Third Branch Inside Diameter:**

0.460 inches as supplied 0.270 inches after unrestricted recovery

**Fourth Branch Inside Diameter:**

0.460 inches as supplied 0.270 inches after unrestricted recovery

**Distance From Intersecting Centerline Of Main Body To End Of Second Branch:**

1.940 inches after unrestricted recovery

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

1.770 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.070 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.060 inches after unrestricted recovery

**Second Branch Wall Thickness:**

0.060 inches after unrestricted recovery

**Third Branch Wall Thickness:**

0.060 inches after unrestricted recovery

**Fourth Branch Wall Thickness:**

0.060 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:**

1.420 inches after unrestricted recovery

**Angle Between Main Body And First Branch Centerlines In Deg:**

10.0 as supplied 45.0 after unrestricted recovery

**Angle Between Main Body And Second Branch Centerlines In Deg:**

10.0 as supplied 15.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Plastic, polychloroprene, mil-i-81765/2

**Material:**

Plastic, polychloroprene, mil-i-81765/2

**Style Designator:**

Transition-1 to 4 cables

**Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500