

View Online at <https://aerobasegroup.com/nsn/5970-01-348-4761>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Wall Thickness:

0.070 inches after unrestricted recovery

Main Bodylength:

2.640 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.220 inches as supplied 0.220 inches after unrestricted recovery

Main Body Large End Inside Diameter:

1.220 inches as supplied 0.650 inches after unrestricted recovery

Distance From Bottom Of Shoulder To Large End Of Main Body:

1.380 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

0.710 inches after unrestricted recovery

Min. Tensile Strength (psi):

2000 pounds per square inch

Special Features:

Btab located between exterior small dia. And large dia. With hole 0.080 in. Dia; inside diameter of large end has lips; wall thickness on small end tapers to 0.040 in.; inside coated with adhesive

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corp

Material:

Plastic, polyolefin, rt-301, raychem corp

Style Designator:

Boot-straight

Dielectric Material Voltage Rating Per Unit Thickness:

300.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500