

View Online at <https://aerobasegroup.com/nsn/5970-01-348-8251>

**Reliability Indicator:**

Not established

**Temperature Rating:**

-55.0 degrees celsius and 135.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

**Main Body Wall Thickness:**

0.130 inches after unrestricted recovery

**Main Bodylength:**

5.120 inches after unrestricted recovery

**Main Body Small End Inside Diameter:**

2.360 inches as supplied0.560 inches after unrestricted recovery

**Main Body Large End Inside Diameter:**

2.360 inches as supplied1.320 inches after unrestricted recovery

**Distance From Bottom Of Shoulder To Large End Of Main Body:**

2.830 inches after unrestricted recovery

**Distance From Top Of Shoulder To Small End Of Main Body:**

1.500 inches after unrestricted recovery

**Min. Tensile Strength (psi):**

2000 pounds per square inch

**Special Features:**

Tab located between exterior small dia. And large dia. With hole 0.080 in. Dia; inside diameter of large end has lips; wall thickness on small end tapers to 0.060 in.; inside coated with adhesive

**Flexibility:**

Semirigid

**Color:**

Black

**Material:**

Plastic, polyolefin, rt-301, raychem corp

**Material:**

Plastic, polyolefin, rt-301, raychem corp

**Style Designator:**

Boot-straight

**Dielectric Material Voltage Rating Per Unit Thickness:**

300.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500