## NSN 5970-01-352-6536

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-352-6536 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Main Body Wall Thickness: 0.150 inches after unrestricted recovery Main Bodylength: 6.900 inches after unrestricted recovery Main Body Small End Inside Diameter: 2.094 inches as supplied0.700 inches after unrestricted recovery Main Body Large End Inside Diameter: 2.094 inches as supplied1.130 inches after unrestricted recovery Distance From Bottom Of Shoulder To Large End Of Main Body: 1.730 inches after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 1.880 inches after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Large end has lip; small end wall thk 0.080 in. After recovery; inside adhesive coated Flexibility: Semirigid Color: Black Material: Plastic, polyolefin, rt-301, raychem corp Material: Plastic, polyolefin, rt-301, raychem corp **Style Designator:** Boot-straight **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A22500