# NSN 5970-01-353-5764

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-353-5764

# **Reliability Indicator:**

Not established

#### **Tempurature Rating:**

-55.0 degrees celsius and 225.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and corrosion resistant and water resistant

#### Main Body Inside Diameter:

1.060 inches as supplied0.490 inches after unrestricted recovery

#### First Branch Inside Diameter:

0.520 inches as supplied0.240 inches after unrestricted recovery

#### **Second Branch Inside Diameter:**

0.520 inches as supplied0.240 inches after unrestricted recovery

#### **Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

1.700 inches after unrestricted recovery

#### Main Body Wall Thickness:

0.100 inches after unrestricted recovery

#### First Branch Wall Thickness:

0.060 inches after unrestricted recovery

#### **Second Branch Wall Thickness:**

0.060 inches after unrestricted recovery

# **Distance From Edge Of Main Body To Intersecting Centerlines:**

1.500 inches after unrestricted recovery

#### Angle Between Main Body And Second Branch Centerlines In Deg:

10.0 as supplied22.5 after unrestricted recovery

## Min. Tensile Strength (psi):

1200 pounds per square inch

# **Special Features:**

Inside adhesive coating

#### Flexibility:

Flexible

# Color:

Black

### Material:

Plastic, polyolefin, rt-1304, raychem corp

#### Material:

Plastic, polyolefin, rt-1304, raychem corp

## Style Designator:

Transition-y

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5970-01-353-5764

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



em			

No

Fiig:

A22500