

View Online at <https://aerobasegroup.com/nsn/5970-01-354-9056>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-55.0 degrees celsius and 135.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and water resistant

**Distance From Centerline Of Main Body To End Of First Branch:**

1.040 inches after unrestricted recovery

**Main Body Inside Diameter:**

0.260 inches as supplied 0.120 inches after unrestricted recovery

**First Branch Inside Diameter:**

0.520 inches as supplied 0.240 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.040 inches as supplied 0.040 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.060 inches as supplied 0.060 inches after unrestricted recovery

**Main Bodylength:**

1.410 inches after unrestricted recovery

**Angle Between Main Body And First Branch Centerlines In Deg:**

120.0 as supplied 90.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

1200 pounds per square inch

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Plastic, polyolefin, mil-i-81765/1, type ii

**Material:**

Plastic, polyolefin, mil-i-81765/1, type ii

**Style Designator:**

Transition-t

**Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500