# NSN 5970-01-354-9056

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-354-9056

# **Reliability Indicator:**

Not established

### **Tempurature Rating:**

-55.0 degrees celsius and 135.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and water resistant

### Distance From Centerline Of Main Body To End Of First Branch:

1.040 inches after unrestricted recovery

### Main Body Inside Diameter:

0.260 inches as supplied0.120 inches after unrestricted recovery

#### **First Branch Inside Diameter:**

0.520 inches as supplied0.240 inches after unrestricted recovery

### Main Body Wall Thickness:

0.040 inches as supplied0.040 inches after unrestricted recovery

### First Branch Wall Thickness:

0.060 inches as supplied0.060 inches after unrestricted recovery

### Main Bodylength:

1.410 inches after unrestricted recovery

# Angle Between Main Body And First Branch Centerlines In Deg:

120.0 as supplied90.0 after unrestricted recovery

# Min. Tensile Strength (psi):

1200 pounds per square inch

# Flexibility:

Flexible

# Color:

Black

## Material:

Plastic, polyolefin, mil-i-81765/1, type ii

# Material:

Plastic, polyolefin, mil-i-81765/1, type ii

## **Style Designator:**

Transition-t

### **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

### Shelf Life:

N/a

#### **Unit Of Measure:**

--

## Demilitarization:

No

### Fiig:

A22500