NSN 5970-01-355-4465

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-355-4465
Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius and 225.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Wall Thickness:
0.090 inches after unrestricted recovery
Main Bodylength:
2.320 inches after unrestricted recovery
Main Body Small End Inside Diameter:
1.630 inches as supplied0.390 inches after unrestricted recovery
Main Body Large End Inside Diameter:
1.630 inches as supplied1.110 inches after unrestricted recovery
Distance From Bottom Of Shoulder To Large End Of Main Body:
0.820 inches after unrestricted recovery
Distance From Top Of Shoulder To Small End Of Main Body:
0.790 inches after unrestricted recovery
Min. Tensile Strength (psi):
1200 pounds per square inch
Special Features:
Tab located between exterior small diameter and large diameter with hole 0.080 in. Dia; inside diameter has lips; wall thickness on small diameter and large diameter with hole 0.080 in. Dia; inside diameter has lips; wall thickness on small diameter and large diameter with hole 0.080 in. Dia; inside diameter has lips; wall thickness on small diameter and large diameter with hole 0.080 in. Dia; inside diameter has lips; wall thickness on small diameter and large diameter with hole 0.080 in. Dia; inside diameter has lips; wall thickness on small diameter with hole 0.080 in.
end tapers to 0.040 in.
Flexibility:
Flexible
Color:
Black
Material:
Plastic, polyolefin, rt-1304, raychem corp
Material:
Plastic, polyolefin, rt-1304, raychem corp
Style Designator:
Boot-straight
Dielectric Material Voltage Rating Per Unit Thickness:
225.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:

Fiig: A22500

No

Demilitarization: