

View Online at <https://aerobasegroup.com/nsn/5970-01-355-7257>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Distance From Centerline Of Main Body To End Of First Branch:

2.140 inches after unrestricted recovery

Main Body Inside Diameter:

0.520 inches as supplied 0.240 inches after unrestricted recovery

First Branch Inside Diameter:

1.060 inches as supplied 0.490 inches after unrestricted recovery

Main Body Wall Thickness:

0.060 inches as supplied 0.060 inches after unrestricted recovery

First Branch Wall Thickness:

0.100 inches as supplied 0.100 inches after unrestricted recovery

Main Bodylength:

2.640 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

120.0 as supplied 90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin, mil-i-81765/1, type ii

Material:

Plastic, polyolefin, mil-i-81765/1, type ii

Style Designator:

Transition-t

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500