

View Online at <https://aerobasegroup.com/nsn/5970-01-358-9393>

**Wall Thickness:**

Between 0.030 inches and 0.040 inches

**Reliability Indicator:**

Not established

**Inside Diameter:**

Between 1.000 inches and 1.036 inches

**Overall Length:**

Any acceptable

**Temperature Rating:**

-46.0 degrees celsius and 70.0 degrees celsius

**Environmental Protection:**

Flame resistant and mildew resistant and oil resistant

**End Application:**

Support equipment, mx peacekeeper missile

**Min. Tensile Strength (psi):**

1450 pounds per square inch

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Plastic, mil-i-631, type f, form u, subform ua, grade b, class 1, category 1

**Style Designator:**

Nonshrinkable

**Dielectric Material Voltage Rating Per Unit Thickness:**

520.0 volts per military /0.001 inch/

**Specification Or Standard:**

1 category and 1 class and u form and b grade and 1 in. Awg size and ua subform and f type

**Departure From Cited Document:**

As modified by color

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500

**Mil-std (military Standard):**

Mil-i-631 spec.