Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-359-2682

Deliekiliku Indiaetan
Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius and 135.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and water resistant
Main Body Wall Thickness:
0.070 inches after unrestricted recovery
Main Bodylength:
3.320 inches after unrestricted recovery
Main Body Small End Inside Diameter:
0.380 inches as supplied0.120 inches after unrestricted recovery
Main Body Large End Inside Diameter:
1.350 inches as supplied1.020 inches after unrestricted recovery
Distance From Bottom Of Shoulder To Large End Of Main Body:
0.900 inches after unrestricted recovery
End Application:
Low altitude navigation and targeting infrared system
Min. Tensile Strength (psi):
1200 pounds per square inch
Special Features:
Inside adhesive coated
Flexibility:
Flexible
Color:
Black
Material:
Plastic, polyolefin, rt-1304, raychem corp
Material:
Plastic, polyolefin, rt-1304, raychem corp
Style Designator:
Boot-straight-long
Dielectric Material Voltage Rating Per Unit Thickness:
225.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A22500