Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-359-5317

Reliability Ind	icator:
Not establishe	d
Tempurature	Rating:
-55.0 degrees	celsius and 225.0 degrees celsius
Environmenta	al Protection:
Corrosion resis	stant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Wa	all Thickness:
0.070 inches	after unrestricted recovery
Main Bodylen	gth:
3.130 inches	after unrestricted recovery
Main Body Sn	nall End Inside Diameter:
0.390 inches	as supplied0.140 inches after unrestricted recovery
Main Body La	rge End Inside Diameter:
1.660 inches	as supplied1.340 inches after unrestricted recovery
Distance Fror	n Bottom Of Shoulder To Large End Of Main Body:
	after unrestricted recovery
Min. Tensile S	
	ber square inch
Special Featu	-
-	lip; wall thickness on small end tapers to 0.045 in.; inside adhesive coated
Flexibility:	
Flexible	
Color:	
Black	
Material:	
Plastic, polyole	fin, rt-1304, raychem corp
Material:	
Plastic, polvole	fin, rt-1304, raychem corp
Style Designa	
Boot-straight-lo	
-	erial Voltage Rating Per Unit Thickness:
	military /0.001 inch/
Shelf Life:	
N/a	
Unit Of Measu	ıre:
Demilitarizatio	on:
No	
Fiig:	
A22500	