Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-363-8275

| I | Dielectric Withstanding Voltage In Volts:                    |
|---|--|
| Ę | 500.0  |
| F | Reliability Indicator:                                       |
| 1 | Not established  |
| ( | Overall Length:  |
| ł | Any acceptable   |
| ٦ | Tempurature Rating:  |
|   | 55.0 degrees celsius and 175.0 degrees celsius               |
| ł | Environmental Protection:                                    |
| ( | Corrosion resistant and flame resistant and mildew resistant |
| ł | Expanded Inside Diameter:                                    |
| ( | 0.093 inches   |
| F | Recovered Inside Diameter:                                   |
| ( | 0.046 inches   |
| ł | Recovered Wall Thickness:                                    |
| ( | 0.020 inches   |
| ľ | Nin. Tensile Strength (psi):                                 |
| 2 | 2000 pounds per square inch                                  |
| ł | Flexibility:   |
| F | Flexible   |
| ( | Color:   |
| E | Black  |
| I | Material:  |
| F | Plastic, polyolefin  |
| ľ | Material:  |
| F | Plastic polyolefin   |
| ę | Style Designator:  |
| Ş | Shrinkable   |
| ç | Shelf Life:  |
| ١ | N/a  |
| ι | Jnit Of Measure:   |
| - | -  |
| I | Demilitarization:  |
| 1 | No   |
| ł | Filg:  |
|   | 422500   |