Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-364-4023

Reliability Indicator:
Not established
Large End Wall Thickness Of Main Body:
0.080 inches after unrestricted recovery
Small End Wall Thickness Of Main Body:
0.150 inches after unrestricted recovery
Distance From Intersecting Centerlines To Edge Of Small End:
3.840 inches after unrestricted recovery
Distance From Centerline Of Small End To Edge Of Large End:
1.640 inches after unrestricted recovery
Main Body Small End Inside Diameter:
2.600 inches as supplied0.800 inches after unrestricted recovery
Main Body Large End Inside Diameter:
2.600 inches as supplied1.750 inches after unrestricted recovery
Distance From Top Of Shoulder To Small End Of Main Body:
1.580 inches after unrestricted recovery
Angle Between Large End And Small End Centerlines In Deg:
90.0 after unrestricted recovery
Special Features:
Drain holes are included; large end has lip
Flexibility:
Flexible
Height:
2.600 inches after unrestricted recovery
Color:
Black
Material:
Plastic, polyolefin, rt-1304, rayclad tubes inc
Material:
Plastic, polyolefin, rt-1304, rayclad tubes inc
Style Designator:
Boot-90 degrees
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A22500