Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-365-9142

View Online at https://aerobasegroup.com/nsn/5970-01-365-9142
Reliability Indicator:
Not established
Tempurature Rating:
-75.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Large End Wall Thickness Of Main Body:
0.100 inches after unrestricted recovery
Small End Wall Thickness Of Main Body:
0.100 inches after unrestricted recovery
Distance From Intersecting Centerlines To Edge Of Small End:
3.225 inches as supplied2.910 inches after unrestricted recovery
Distance From Centerline Of Small End To Edge Of Large End:
1.575 inches as supplied1.260 inches after unrestricted recovery
Main Body Small End Inside Diameter:
1.250 inches as supplied0.620 inches after unrestricted recovery
Main Body Large End Inside Diameter:
1.250 inches as supplied0.620 inches after unrestricted recovery
Angle Between Large End And Small End Centerlines In Deg:
90.0 after unrestricted recovery
Min. Tensile Strength (psi):
600 pounds per square inch
Flexibility:
Flexible
Color:
Black
Material:
Rubber, silicone, rt-602, raychem corp
Material:
Rubber, silicone, rt-602, raychem corp
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life: N/a
Unit Of Measure:
Unit Of Measure.
 Demilitarization:
No
Fiig:
A22500