Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-365-9143

| view Online at https://aerobasegroup.com/nsn/5970-01-505-9145  |
|--|
| Reliability Indicator:   |
| Not established  |
| Tempurature Rating:  |
| -75.0 degrees celsius  |
| Environmental Protection:  |
| Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant |
| Large End Wall Thickness Of Main Body:   |
| 0.100 inches after unrestricted recovery   |
| Small End Wall Thickness Of Main Body:   |
| 0.100 inches after unrestricted recovery   |
| Distance From Intersecting Centerlines To Edge Of Small End:   |
| 3.350 inches as supplied 3.035 inches after unrestricted recovery                                      |
| Distance From Centerline Of Small End To Edge Of Large End:  |
| 1.700 inches as supplied 1.385 inches after unrestricted recovery                                      |
| Main Body Small End Inside Diameter:   |
| 1.500 inches as supplied0.870 inches after unrestricted recovery                                       |
| Main Body Large End Inside Diameter:   |
| 1.500 inches as supplied0.870 inches after unrestricted recovery                                       |
| Angle Between Large End And Small End Centerlines In Deg:  |
| 90.0 after unrestricted recovery   |
| Min. Tensile Strength (psi):   |
| 600 pounds per square inch   |
| Flexibility:   |
| Flexible   |
| Color:   |
| Black  |
| Material:  |
| Rubber, silicone, rt-602, raychem corp   |
| Material:  |
| Rubber, silicone, rt-602, raychem corp   |
| Dielectric Material Voltage Rating Per Unit Thickness:   |
| 200.0 volts per military /0.001 inch/  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Filg:  |
| A22500   |