Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-365-9144

**Reliability Indicator:** Not established **Tempurature Rating:** -75.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant Large End Wall Thickness Of Main Body: 0.100 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.100 inches after unrestricted recovery **Distance From Intersecting Centerlines To Edge Of Small End:** 3.600 inches as supplied 3.225 inches after unrestricted recovery Distance From Centerline Of Small End To Edge Of Large End: 1.950 inches as supplied1.575 inches after unrestricted recovery Main Body Small End Inside Diameter: 2.000 inches as supplied1.250 inches after unrestricted recovery Main Body Large End Inside Diameter: 2.000 inches as supplied 1.250 inches after unrestricted recovery Angle Between Large End And Small End Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 600 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, silicone, rt-602, raychem corp Material: Rubber, silicone, rt-602, raychem corp **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A22500