# NSN 5970-01-366-0726

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-366-0726

# **Reliability Indicator:**

Not established

#### **Tempurature Rating:**

-55.0 degrees celsius and 135.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and water resistant

# Large End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

#### Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

#### Main Bodylength:

6.780 inches after unrestricted recovery

#### Main Body Small End Inside Diameter:

1.340 inches as supplied0.380 inches after unrestricted recovery

# **Main Body Large End Inside Diameter:**

1.340 inches as supplied0.900 inches after unrestricted recovery

#### Distance From Top Of Shoulder To Small End Of Main Body:

Any acceptable as supplied

# **End Largest Diameter:**

Any acceptable as supplied

# Min. Tensile Strength (psi):

1200 pounds per square inch

#### Lip Height:

0.120 inches after unrestricted recovery

#### Lip Width:

0.040 inches after unrestricted recovery

# **Special Features:**

Red color stripe; inside adhesive coated; 4 drain holes included

#### Flexibility:

Flexible

# Height:

0.860 inches after unrestricted recovery

# Color:

Black

#### Material:

Plastic, polyolefin, mil-i-81765/1 type ii

#### Material:

Plastic, polyolefin, mil-i-81765/1 type ii

# **Style Designator:**

Boot-90 degrees

# **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# NSN 5970-01-366-0726

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



| Shelf Life:      |
|------------------|
| N/a              |
| Unit Of Measure: |
|                  |

Demilitarization:

No

Fiig:

A22500