

View Online at <https://aerobasegroup.com/nsn/5970-01-366-0726>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Large End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

Main Bodylength:

6.780 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.340 inches as supplied0.380 inches after unrestricted recovery

Main Body Large End Inside Diameter:

1.340 inches as supplied0.900 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

Any acceptable as supplied

End Largest Diameter:

Any acceptable as supplied

Min. Tensile Strength (psi):

1200 pounds per square inch

Lip Height:

0.120 inches after unrestricted recovery

Lip Width:

0.040 inches after unrestricted recovery

Special Features:

Red color stripe; inside adhesive coated; 4 drain holes included

Flexibility:

Flexible

Height:

0.860 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin, mil-i-81765/1 type ii

Material:

Plastic, polyolefin, mil-i-81765/1 type ii

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500