

View Online at <https://aerobasegroup.com/nsn/5970-01-367-8794>

Reliability Indicator:

Not established

Tempurature Rating:

135.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Inside Diameter:

1.200 inches as supplied 0.620 inches after unrestricted recovery

First Branch Inside Diameter:

0.800 inches as supplied 0.420 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

2.000 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.070 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.250 inches after unrestricted recovery

Main Bodylength:

3.250 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

10.0 as supplied 30.0 after unrestricted recovery

Min. Tensile Strength (psi):

600 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Rubber, silicone, rt-602, rayclad tubes inc

Material:

Rubber, silicone, rt-602, rayclad tubes inc

Style Designator:

Transition-45 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500