

View Online at <https://aerobasegroup.com/nsn/5970-01-369-9903>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-55.0 degrees celsius

**Environmental Protection:**

Chemical resistant and corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

**Large End Wall Thickness Of Main Body:**

0.040 inches after unrestricted recovery

**Small End Wall Thickness Of Main Body:**

0.045 inches after unrestricted recovery

**Main Bodylength:**

6.780 inches after unrestricted recovery

**Main Body Small End Inside Diameter:**

1.340 inches as supplied0.380 inches after unrestricted recovery

**Main Body Large End Inside Diameter:**

1.340 inches as supplied0.900 inches after unrestricted recovery

**Distance From Top Of Shoulder To Small End Of Main Body:**

5.220 inches after unrestricted recovery

**End Largest Diameter:**

0.900 inches after unrestricted recovery

**Min. Tensile Strength (psi):**

1200 pounds per square inch

**Lip Height:**

0.120 inches after unrestricted recovery

**Lip Width:**

0.070 inches after unrestricted recovery

**Special Features:**

Inside adhesive coated; large end has lip

**Flexibility:**

Flexible

**Height:**

0.860 inches after unrestricted recovery

**Color:**

Black

**Material:**

Plastic, polyolefin, rt-1304, raychem corp

**Material:**

Plastic, polyolefin, rt-1304, raychem corp

**Style Designator:**

Boot-90 degrees

**Dielectric Material Voltage Rating Per Unit Thickness:**

225.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500