

View Online at https://aerobasegroup.com/nsn/5970-01-369-9903

view Online at https://aerobasegroup.com/nsn/5970-01-369-9903
Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Chemical resistant and corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Large End Wall Thickness Of Main Body:
0.040 inches after unrestricted recovery
Small End Wall Thickness Of Main Body:
0.045 inches after unrestricted recovery
Main Bodylength:
6.780 inches after unrestricted recovery
Main Body Small End Inside Diameter:
1.340 inches as supplied0.380 inches after unrestricted recovery
Main Body Large End Inside Diameter:
1.340 inches as supplied0.900 inches after unrestricted recovery
Distance From Top Of Shoulder To Small End Of Main Body:
5.220 inches after unrestricted recovery
End Largest Diameter:
0.900 inches after unrestricted recovery
Min. Tensile Strength (psi):
1200 pounds per square inch
Lip Height:
0.120 inches after unrestricted recovery
Lip Width:
0.070 inches after unrestricted recovery
Special Features:
Inside adhesive coated; large end has lip
Flexibility:
Flexible
Height:
0.860 inches after unrestricted recovery
Color:
Black
Material:
Plastic, polyolefin, rt-1304, raychem corp
Material:
Plastic, polyolefin, rt-1304, raychem corp
Style Designator:
Boot-90 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
225.0 volts per military /0.001 inch/

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500