NSN 5970-01-370-5219

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-370-5219

Reliability Indicator:

Not established

Tempurature Rating:

-20.0 degrees celsius

Environmental Protection:

Flame resistant

Large End Wall Thickness Of Main Body:

0.130 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.060 inches after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

3.150 inches after unrestricted recovery

Distance From Centerline Of Small End To Edge Of Large End:

1.380 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.480 inches as supplied

Main Body Large End Inside Diameter:

1.990 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

1.770 inches after unrestricted recovery

Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1000 pounds per square inch

Special Features:

Inside adhesive coated; large end has lip; tab with 0.080 in. Diameter hole on outer wall angle

Flexibility:

Flexible

Height:

2.130 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin, rt-1323, raychem corp

Material:

Plastic, polyolefin, rt-1323, raychem corp

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

380.0 volts per military /0.001 inch/

Shelf Life:

N/a

NSN 5970-01-370-5219

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A22500