

View Online at <https://aerobasegroup.com/nsn/5970-01-371-3971>

**Wall Thickness:**

Between 0.019 inches and 0.029 inches

**Dielectric Withstanding Voltage In Volts:**

15000.0

**Reliability Indicator:**

Not established

**Inside Diameter:**

Between 0.485 inches and 0.500 inches

**Temperature Rating:**

-95.0 degrees fahrenheit and 500.0 degrees fahrenheit

**End Application:**

1560-01-461-7434

**Design Form:**

Full round

**Min. Tensile Strength (psi):**

2500 pounds per square inch

**Product Name:**

Tubing-convoluted, fte-fluorocarbon

**Special Features:**

Large end wall thickness of main body is 0.025 inches after unrestricted recovery; main body large end inside diameter is 0.500 inches after unrestricted recovery; 9 convolutions per in; two 1/8 in diameter drain holes, diametrically opposed, every 6 inches in length of the tube/sleeve

**Flexibility:**

Flexible

**Color:**

Natural

**Material:**

Plastic, polytetrafluoroethylene

**Material:**

Plastic polytetrafluoroethylene

**Style Designator:**

Nonshrinkable

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500