NSN 5970-01-376-5868

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-376-5868

٨	/lair	۱ R	odv	Inc	ahis	Dia	met	٥r-
Ŋ	nan	ıD	uuy	1113	siue	υla	HIEL	SI.

0.830 inches as supplied0.410 inches after unrestricted recovery

First Branch Inside Diameter:

0.510 inches as supplied0.240 inches after unrestricted recovery

Second Branch Inside Diameter:

0.510 inches as supplied0.240 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.730 inches as supplied

Main Body Wall Thickness:

0.080 inches after unrestricted recovery

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

Second Branch Wall Thickness:

0.060 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.500 inches as supplied

Angle Between Main Body And Second Branch Centerlines In Deg:

17.5 after unrestricted recovery

Material:

Polyolefin/copper composite

Material:

Polyolefin/copper composite

Style Designator:

Transition-y

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500