NSN 5970-01-387-6352

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-387-6352

Port 1990 de Port
Reliability Indicator:
Not established
Main Body Inside Diameter:
25.38 millimeters as supplied
First Branch Inside Diameter:
6.1 millimeters after unrestricted recovery
Second Branch Inside Diameter:
6.1 millimeters after unrestricted recovery
Distance From Intersecting Centerline Of Main Body To End Of First Branch:
39.7 millimeters after unrestricted recovery
Main Body Wall Thickness:
2.54 millimeters after unrestricted recovery
First Branch Wall Thickness:
1.52 millimeters after unrestricted recovery
Second Branch Wall Thickness:
1.52 millimeters after unrestricted recovery
Distance From Edge Of Main Body To Intersecting Centerlines:
45.9 millimeters after unrestricted recovery
Angle Between Main Body And Second Branch Centerlines In Deg:
22.5 after unrestricted recovery
Special Features:
Inside adhesive coated
Flexibility:
Flexible
Color:
Black
Material:
Plastic, polyolefin, mil-i-81765/1, type ii
Material:
Plastic, polyolefin, mil-i-81765/1, type ii
Style Designator:
Transition-y
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A22500