

View Online at <https://aerobasegroup.com/nsn/5970-01-392-0002>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-20.0 degrees celsius

**Environmental Protection:**

Flame resistant

**Large End Wall Thickness Of Main Body:**

0.070 inches after unrestricted recovery

**Small End Wall Thickness Of Main Body:**

0.032 inches after unrestricted recovery

**Distance From Intersecting Centerlines To Edge Of Small End:**

1.540 inches after unrestricted recovery

**Distance From Centerline Of Small End To Edge Of Large End:**

0.830 inches after unrestricted recovery

**Main Body Small End Inside Diameter:**

0.650 inches as supplied

**Main Body Large End Inside Diameter:**

1.160 inches as supplied

**Distance From Top Of Shoulder To Small End Of Main Body:**

0.790 inches after unrestricted recovery

**Angle Between Large End And Small End Centerlines In Deg:**

90.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

1000 pounds per square inch

**Special Features:**

Inside adhesive coated; large end has lip; small end wall thickness tapers to 0.016 in.; tab with 0.080 in. Diameter hole on outer wall angle

**Flexibility:**

Flexible

**Height:**

1.220 inches after unrestricted recovery

**Color:**

Black

**Material:**

Plastic, polyolefin, rt-1323, raychem corp

**Material:**

Plastic, polyolefin, rt-1323, raychem corp

**Style Designator:**

Boot-90 degrees

**Dielectric Material Voltage Rating Per Unit Thickness:**

380.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500