NSN 5970-01-414-8814

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-414-8814 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Flame resistant and mildew resistant Distance From Centerline Of Main Body To End Of First Branch: 2.370 inches after unrestricted recovery Main Body Inside Diameter: 1.290 inches as supplied **First Branch Inside Diameter:** 0.840 inches as supplied Main Body Wall Thickness: 0.050 inches after unrestricted recovery **First Branch Wall Thickness:** 0.050 inches after unrestricted recovery Main Bodylength: 4.740 inches after unrestricted recovery **End Application:** Mrap - cougar Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Inside adhesive coated Flexibility: Flexible Color: Black Material: Plastic, elastomeric polymer blend, rt-1321, raychem, corp Plastic, elastomeric polymer blend, rt-1321, raychem, corp **Style Designator:** Transition-t **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5970-01-414-8814

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500