Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-414-8814

Reliability Indicator: Not established Tempurature Rating: -55.0 degrees celsius Environmental Protection: Flame resistant and mildew resistant Distance From Centerline Of Main Body To End Of First Branch: 2.370 inches after unrestricted recovery Main Body Inside Diameter: 1.290 inches as supplied
Tempurature Rating: -55.0 degrees celsius Environmental Protection: Flame resistant and mildew resistant Distance From Centerline Of Main Body To End Of First Branch: 2.370 inches after unrestricted recovery Main Body Inside Diameter:
-55.0 degrees celsius Environmental Protection: Flame resistant and mildew resistant Distance From Centerline Of Main Body To End Of First Branch: 2.370 inches after unrestricted recovery Main Body Inside Diameter:
Environmental Protection: Flame resistant and mildew resistant Distance From Centerline Of Main Body To End Of First Branch: 2.370 inches after unrestricted recovery Main Body Inside Diameter:
Flame resistant and mildew resistant Distance From Centerline Of Main Body To End Of First Branch: 2.370 inches after unrestricted recovery Main Body Inside Diameter:
Distance From Centerline Of Main Body To End Of First Branch: 2.370 inches after unrestricted recovery Main Body Inside Diameter:
2.370 inches after unrestricted recovery Main Body Inside Diameter:
Main Body Inside Diameter:
-
1.290 Inches as supplied
First Branch Inside Diameter:
0.840 inches as supplied
Main Body Wall Thickness:
0.050 inches after unrestricted recovery
First Branch Wall Thickness:
0.050 inches after unrestricted recovery
Main Bodylength:
4.740 inches after unrestricted recovery
End Application:
Mrap - cougar
Min. Tensile Strength (psi):
1500 pounds per square inch
Special Features:
Inside adhesive coated
Flexibility:
Flexible
Color:
Black
Material:
Plastic, elastomeric polymer blend, rt-1321, raychem, corp
Material:
Plastic, elastomeric polymer blend, rt-1321, raychem, corp
Style Designator:
Transition-t
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5970-01-414-8814

Special Purpose Electrical Insulation Sleeving - Page 2 of 2

Fiig: A22500

