

View Online at <https://aerobasegroup.com/nsn/5970-01-416-1732>

Reliability Indicator:

Not established

Tempurature Rating:

-20.0 degrees celsius

Environmental Protection:

Flame resistant

Large End Wall Thickness Of Main Body:

0.050 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.016 inches after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

0.980 inches after unrestricted recovery

Distance From Centerline Of Small End To Edge Of Large End:

0.750 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.890 inches as supplied

Main Body Large End Inside Diameter:

0.890 inches as supplied

Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1000 pounds per square inch

Special Features:

Inside adhesive coated; large end has lip; small end wall thickness tapers to 0.016 in.; tab with 0.060 in. Diameter hole on outer wall angle

Flexibility:

Semiflexible

Height:

0.980 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin, rt-1323, raychem corp

Material:

Plastic, polyolefin, rt-1323, raychem corp

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

380.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500