Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-430-7123

| Reliability Indicator:   |
|--|
| Not established  |
| Overall Length:  |
| Any acceptable   |
| Tempurature Rating:  |
| -67.0 degrees celsius and 200.0 degrees celsius                    |
| Environmental Protection:  |
| Corrosion resistant and flame resistant and mildew resistant       |
| Expanded Inside Diameter:  |
| 2.100 inches   |
| Recovered Inside Diameter:   |
| 1.700 inches   |
| Recovered Wall Thickness:  |
| 0.020 inches   |
| Min. Tensile Strength (psi):                                       |
| 2000 pounds per square inch  |
| Flexibility:   |
| Flexible   |
| Color:   |
| Clear  |
| Material:  |
| Plastic, fluorinated ethylene propylene, mil-dtl-23053/11, class 1 |
| Material:  |
| Plastic fluorinated ethylene propylene                             |
| Style Designator:  |
| Shrinkable   |
| Dielectric Material Voltage Rating Per Unit Thickness:             |
| 500.0 volts per military /0.001 inch/                              |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A22500   |
|  |