Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-432-6466

Poliokility Indicatory
Reliability Indicator: Not established
Tempurature Rating:
-55.0 degrees celsius and 200.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and water resistant
Large End Wall Thickness Of Main Body:
0.060 inches after unrestricted recovery
Small End Wall Thickness Of Main Body:
0.060 inches after unrestricted recovery
Distance From Intersecting Centerlines To Edge Of Small End:
Any acceptable as supplied
Distance From Centerline Of Small End To Edge Of Large End:
Any acceptable as supplied
Main Body Small End Inside Diameter:
0.580 inches as supplied
Main Body Large End Inside Diameter:
1.120 inches as supplied
Distance From Top Of Shoulder To Small End Of Main Body:
Any acceptable as supplied
Angle Between Large End And Small End Centerlines In Deg:
90.0 as supplied
Min. Tensile Strength (psi):
1800 pounds per square inch
Special Features:
Yellow color stripe; large end has lip
Flexibility:
Flexible
Height:
1.070 inches after unrestricted recovery
Color:
Black
Material:
Plastic, fluoroelastomer, mil-i-81765/4
Material:
Plastic, fluoroelastomer, mil-i-81765/4
Style Designator:
Boot-90 degrees
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a

## NSN 5970-01-432-6466

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A22500